National Grid-Upstream HVAC Eligible Product List and Incentives



Qualifying split systems must have both a new condenser and a new coil that meets AHRI specifications and where the matched system performance (condenser and coil) meets or exceeds the minimum SEER/EER/IEER outlined in the table below.

Qualifying units must meet or exceed all SEER, EER, IEER, HSPF, and COP specifications required for their equipment category and unit size.

| Unitary and Split Air Conditioning S | Systems (Air Cooled | d, Including All 1 | Types of Heating) |
|--------------------------------------|---------------------|--------------------|-------------------|
| | | | |

| 1 | Tier I | | Cooling Mode | | Incentive |
|------------------|------------------------|------|--------------|------|-----------|
| Unit Size (Tons) | Unit Size (Btu/hr) | SEER | EER | IEER | \$ / Ton |
| < 5.4 (split) | < 65,000 (split) | 14.0 | 12.0 | | \$70 |
| < 5.4 (packaged) | < 65,000 (packaged) | 14.0 | 11.6 | | \$70 |
| ≥ 5.4 to < 11.25 | ≥ 65,000 to < 135,000 | | 11.5 | 12.8 | \$50 |
| ≥ 11.25 to < 20 | ≥ 135,000 to < 240,000 | | 11.5 | 12.3 | \$50 |
| ≥ 20 to < 63 | ≥ 240,000 to < 760,000 | | 10.3 | 11.1 | \$30 |
| ≥ 63 | ≥ 760,000 | | 9.7 | 10.9 | \$30 |

| Tie | Tier II | | Cooling Mode | | |
|------------------|-------------------------------|------|--------------|------|----------|
| Unit Size (Tons) | Unit Size (Btu/hr) | SEER | EER | IEER | \$ / Ton |
| < 5.4 (split) | < 65,000 (split) | 15.0 | 12.5 | | \$125 |
| < 5.4 (packaged) | < 65,000 (packaged) | 15.0 | 12.0 | | \$125 |
| ≥ 5.4 to < 11.25 | ≥ 65,000 to < 135,000 | | 12.0 | 13.8 | \$80 |
| ≥ 11.25 to < 20 | \geq 135,000 to $<$ 240,000 | | 12.0 | 13.0 | \$80 |
| ≥ 20 to < 63 | ≥ 240,000 to < 760,000 | | 10.6 | 12.1 | \$50 |
| ≥ 63 | ≥ 760,000 | | 10.2 | 11.4 | \$50 |

Unitary Air Conditioning Systems (Evaporatively Cooled, Including All Types of Heating)

| Tier I | | | Cooling Mode | | Incentive |
|------------------|--------------------|------|--------------|------|-----------|
| Unit Size (Tons) | Unit Size (Btu/hr) | SEER | EER | IEER | \$ / Ton |
| ≥ 20 | ≥ 240,000 | | 13.3 | 14.1 | \$80 |

Unitary Air Conditioning Systems (Water Cooled, Including All Types of Heating)

| Tier | l . | | Cooling Mode | | Incentive |
|------------------|--------------------|------|--------------|------|-----------|
| Unit Size (Tons) | Unit Size (Btu/hr) | SEER | EER | IEER | \$ / Ton |
| ≥ 20 | ≥ 240,000 | | 13.8 | 14.6 | \$80 |

National Grid-Upstream HVAC Eligible Product List and Incentives



| Unitary | Heat Pump | Systems | (Air Cooled) |
|-----------|-------------------------------|----------|--------------|
| Ollitai 1 | , i i c at i uiiib | OVOLUIIO | IAII OUUICUI |

| Tier I | | | Cooling Mode | | Heating Mode | | Incentive |
|------------------|------------------------|------|--------------|------|--------------|-----|-----------|
| Unit Size (Tons) | Unit Size (Btu/hr) | SEER | EER | IEER | HSPF | COP | \$ / Ton |
| < 5.4 (split) | < 65,000 (split) | 14.0 | 12.0 | | 8.5 | | \$70 |
| < 5.4 (packaged) | < 65,000 (packaged) | 14.0 | 11.6 | | 8.0 | | \$70 |
| ≥ 5.4 to < 11.25 | ≥ 65,000 to < 135,000 | | 11.5 | 12.1 | | 3.4 | \$50 |
| ≥ 11.25 to < 20 | ≥ 135,000 to < 240,000 | | 11.5 | 11.7 | | 3.2 | \$50 |
| ≥ 20 | ≥ 240,000 | | 10.5 | 10.7 | | 3.2 | \$30 |

| 7 | ier II | | Cooling Mode | Э | Heatin | g Mode | Incentive |
|------------------|------------------------|------|--------------|------|--------|--------|-----------|
| Unit Size (Tons) | Unit Size (Btu/hr) | SEER | EER | IEER | HSPF | COP | \$ / Ton |
| < 5.4 (split) | < 65,000 (split) | 15.0 | 12.5 | | 9.0 | | \$125 |
| < 5.4 (packaged) | < 65,000 (packaged) | 15.0 | 12.0 | | 8.5 | | \$125 |
| ≥ 5.4 to < 11.25 | ≥ 65,000 to < 135,000 | | 12.0 | | | 3.4 | \$80 |
| ≥ 11.25 to < 20 | ≥ 135,000 to < 240,000 | | 12.0 | | | 3.2 | \$80 |
| ≥ 20 | ≥ 240,000 | | 10.8 | | | 3.2 | \$50 |

Unitary Heat Pump Systems (Water Source)

| Tier I | | Cooling Mode | | Heating Mode | | Incentive |
|------------------|--------------------|--------------|------|--------------|-----|-----------|
| Unit Size (Tons) | Unit Size (Btu/hr) | SEER | EER | HSPF | COP | \$ / Ton |
| < 11.25 | < 135,000 | | 14.0 | | 4.6 | \$80 |

Groundwater-Water Source Heat Pump Equipment (Open Loop)

| Tier I | | Cooling N | /lode | Heating | g Mode | Incentive |
|------------------|--------------------|-----------|-------|---------|--------|-----------|
| Unit Size (Tons) | Unit Size (Btu/hr) | SEER | EER | HSPF | COP | \$ / Ton |
| < 11.25 | < 135,000 | | 18.0 | | 4.0 | \$150 |

Ground Loop-Water Source Heat Pump Equipment (Closed Loop)

| Tie | er I | Cooling Mode | | Heating | g Mode | Incentive |
|------------------|--------------------|--------------|------|---------|--------|-----------|
| Unit Size (Tons) | Unit Size (Btu/hr) | SEER | EER | HSPF | COP | \$ / Ton |
| < 11.25 | < 135,000 | | 15.0 | | 3.2 | \$150 |

Energy Savings Control and Fan Motor Options-When Installed with New Qualifying Equipment

| Unit | Description | Incentive |
|-----------------------------|---|-----------|
| Dual Enthalpy Economizer | Outside air economizer utilizing 2 enthalpy sensors (1 for outdoor and 1 for return air) | \$250 |
| Demand Control Ventilation* | Outside air intake controlled based on CO ₂ sensor | \$200 |
| ECM Fan** | ECM motors installed on fan powered terminal boxes, fan coils, or HVAC supply fans on small unitary equipment | \$150 |

^{*} Where not required by building code

^{**} For ECM Motors on Fan Powered Boxes & Fan Coils, provide a list detailing the associated HVAC